

---

# **B2\_Command\_Line\_Tool Documentation**

***Release 2.3.0***

**Backblaze**

**Mar 25, 2021**



# CONTENTS

1	Documentation index	3
2	Indices and tables	21



The command-line tool that gives easy access to all of the capabilities of B2 Cloud Storage.

This program provides command-line access to the B2 service.



## DOCUMENTATION INDEX

### 1.1 Authorize-account command

Prompts for Backblaze `applicationKeyId` and `applicationKey` (unless they are given on the command line).

You can authorize with either the master application key or a normal application key.

To use the master application key, provide the application key ID and application key from the B2 Cloud Storage Buckets page on the web site: [https://secure.backblaze.com/b2\\_buckets.htm](https://secure.backblaze.com/b2_buckets.htm)

To use a normal application key, created with the `create-key` command or on the web site, provide the application key ID and the application key itself.

You can also optionally provide application key ID and application key using environment variables `B2_APPLICATION_KEY_ID` and `B2_APPLICATION_KEY` respectively.

Stores an account auth token in `~/.b2_account_info` by default, or the file specified by the `B2_ACCOUNT_INFO` environment variable.

Requires capability:

- **listBuckets**

```
b2 authorize-account [-h] [applicationKeyId] [applicationKey]
```

#### 1.1.1 Positional Arguments

**applicationKeyId**

**applicationKey**

### 1.2 Cancel-all-unfinished-large-files command

Lists all large files that have been started but not finished and cancels them. Any parts that have been uploaded will be deleted.

Requires capability:

- **listFiles**
- **writeFiles**

```
b2 cancel-all-unfinished-large-files [-h] bucketName
```

### 1.2.1 Positional Arguments

**bucketName**

## 1.3 Cancel-large-file command

Cancels a large file upload. Used to undo a `start-large-file`.

Cannot be used once the file is finished. After finishing, using `delete-file-version` to delete the large file.

Requires capability:

- **writeFiles**

```
b2 cancel-large-file [-h] fileId
```

### 1.3.1 Positional Arguments

**fileId**

## 1.4 Clear-account command

Erases everything in `~/ .b2_account_info`. Location of file can be overridden by setting `B2_ACCOUNT_INFO`.

```
b2 clear-account [-h]
```

## 1.5 Copy-file-by-id command

Copy a file version to the given bucket (server-side, **not** via download+upload). Copies the contents of the source B2 file to destination bucket and assigns the given name to the new B2 file.

By default, it copies the file info and content type. You can replace those by setting the `metadataDirective` to `replace`.

`--contentType` and `--info` should only be provided when `--metadataDirective` is set to `replace` and should not be provided when `--metadataDirective` is set to `copy`.

`--contentType` and `--info` are optional. If not set, they will be set based on the source file.

By default, the whole file gets copied, but you can copy an (inclusive!) range of bytes from the source file to the new file using `--range` option.

Each `--info` entry is in the form `a=b`, you can specify many.



The maximum file size is 5GB or 10TB, depending on capability of installed b2sdk version.

To request SSE-B2 encryption for destination files, please set `--destinationServerSideEncryption=SSE-B2`. The default algorithm is set to AES256 which can be changed with `--destinationServerSideEncryptionAlgorithm` parameter.

Requires capability:

- **readFiles** (if `sourceFileId` bucket is private)
- **writeFiles**

```
b2 copy-file-by-id [-h] [--metadataDirective {copy,replace}]
                  [--contentType CONTENTTYPE] [--range RANGE] [--info INFO]
                  [--destinationServerSideEncryption {SSE-B2}]
                  [--destinationServerSideEncryptionAlgorithm {AES256}]
                  sourceFileId destinationBucketName b2FileName
```

### 1.5.1 Positional Arguments

**sourceFileId**

**destinationBucketName**

**b2FileName**

### 1.5.2 Named Arguments

**--metadataDirective** Possible choices: copy, replace

**--contentType**

**--range**

**--info** Default: []

**--destinationServerSideEncryption** Possible choices: SSE-B2

**--destinationServerSideEncryptionAlgorithm** Possible choices: AES256  
Default: "AES256"

## 1.6 Create-bucket command

Creates a new bucket. Prints the ID of the bucket created.

Optionally stores bucket info, CORS rules and lifecycle rules with the bucket. These can be given as JSON on the command line.

If you want server-side encryption for all of the files that are uploaded to a bucket, you can enable SSE-B2 encryption as a default setting for the bucket. In order to do that pass `--defaultServerSideEncryption=SSE-B2`. The default algorithm is set to AES256 which can be changed with `--defaultServerSideEncryptionAlgorithm` parameter. All uploads to that bucket, from the time default encryption is enabled onward, will then be encrypted with SSE-B2 by default.

To disable default bucket encryption, use `--defaultServerSideEncryption=none`.

If `--defaultServerSideEncryption` is not provided, default server side encryption is determined by the server.

---

**Note:** Note that existing files in the bucket are not affected by default bucket encryption settings.

---

Requires capability:

- **writeBuckets**
- **readBucketEncryption**
- **writeBucketEncryption**

```
b2 create-bucket [-h] [--bucketInfo BUCKETINFO] [--corsRules CORSRULES]
                  [--lifecycleRules LIFECYCLERULES]
                  [--defaultServerSideEncryption {SSE-B2,none}]
                  [--defaultServerSideEncryptionAlgorithm {AES256}]
                  bucketName bucketType
```

### 1.6.1 Positional Arguments

**bucketName**

**bucketType**

### 1.6.2 Named Arguments

**--bucketInfo**

**--corsRules**

**--lifecycleRules**

**--defaultServerSideEncryption** Possible choices: SSE-B2, none

**--defaultServerSideEncryptionAlgorithm** Possible choices: AES256

Default: "AES256"

## 1.7 Create-key command

Creates a new application key. Prints the application key information. This is the only time the application key itself will be returned. Listing application keys will show their IDs, but not the secret keys.

The capabilities are passed in as a comma-separated list, like `readFiles,writeFiles`.

The `duration` is the length of time the new application key will exist. When the time expires the key will disappear and will no longer be usable. If not specified, the key will not expire.

The `bucket` is the name of a bucket in the account. When specified, the key will only allow access to that bucket.

The `namePrefix` restricts file access to files whose names start with the prefix.

The output is the new application key ID, followed by the application key itself. The two values returned are the two that you pass to `authorize-account` to use the key.

Requires capability:

- **writeKeys**

```
b2 create-key [-h] [--bucket BUCKET] [--namePrefix NAMEPREFIX]
              [--duration DURATION]
              keyName capabilities
```

### 1.7.1 Positional Arguments

**keyName**

**capabilities**

### 1.7.2 Named Arguments

**--bucket**

**--namePrefix**

**--duration**

## 1.8 Delete-bucket command

Deletes the bucket with the given name.

Requires capability:

- **deleteBuckets**

```
b2 delete-bucket [-h] bucketName
```

### 1.8.1 Positional Arguments

**bucketName**

## 1.9 Delete-file-version command

Permanently and irrevocably deletes one version of a file.

Specifying the `fileName` is more efficient than leaving it out. If you omit the `fileName`, it requires an initial query to B2 to get the file name, before making the call to delete the file. This extra query requires the `readFiles` capability.

Requires capability:

- **deleteFiles**
- **readFiles** (if file name not provided)

```
b2 delete-file-version [-h] [fileName] fileId
```

### 1.9.1 Positional Arguments

**fileName**

**fileId**

## 1.10 Delete-key command

Deletes the specified application key by its ID.

Requires capability:

- **deleteKeys**

```
b2 delete-key [-h] applicationKeyId
```

### 1.10.1 Positional Arguments

**applicationKeyId**

## 1.11 Download-file-by-id command

Downloads the given file, and stores it in the given local file.

If the `tqdm` library is installed, progress bar is displayed on stderr. Without it, simple text progress is printed. Use `--noProgress` to disable progress reporting.

Requires capability:

- **readFiles**

```
b2 download-file-by-id [-h] [--noProgress] fileId localFileName
```

### 1.11.1 Positional Arguments

**fileId**

**localFileName**

### 1.11.2 Named Arguments

**--noProgress**      Default: False

## 1.12 Download-file-by-name command

Downloads the given file, and stores it in the given local file.

If the `tqdm` library is installed, progress bar is displayed on `stderr`. Without it, simple text progress is printed. Use `--noProgress` to disable progress reporting.

Requires capability:

- **readFiles**

```
b2 download-file-by-name [-h] [--noProgress]
                        bucketName b2FileName localFileName
```

### 1.12.1 Positional Arguments

**bucketName**

**b2FileName**

**localFileName**

### 1.12.2 Named Arguments

**--noProgress**      Default: False

## 1.13 Get-account-info command

Shows the account ID, key, auth token, URLs, and what capabilities the current application keys has.

```
b2 get-account-info [-h]
```

## 1.14 Get-bucket command

Prints all of the information about the bucket, including bucket info, CORS rules and lifecycle rules.

If `--showSize` is specified, then display the number of files (`fileCount`) in the bucket and the aggregate size of all files (`totalSize`). Hidden files and hide markers are accounted for in the reported number of files, and hidden files also contribute toward the reported aggregate size, whereas hide markers do not. Each version of a file counts as an individual file, and its size contributes toward the aggregate size. Analysis is recursive.

---

**Note:** Note that `--showSize` requires multiple API calls, and will therefore incur additional latency, computation, and Class C transactions.

---

Requires capability:

- **listBuckets**

```
b2 get-bucket [-h] [--showSize] bucketName
```

### 1.14.1 Positional Arguments

**bucketName**

### 1.14.2 Named Arguments

**--showSize**            Default: False

## 1.15 Get-download-auth command

Prints an authorization token that is valid only for downloading files from the given bucket.

The token is valid for the duration specified, which defaults to 86400 seconds (one day).

Only files that match that given prefix can be downloaded with the token. The prefix defaults to “”, which matches all files in the bucket.

Requires capability:

- **shareFiles**

```
b2 get-download-auth [-h] [--prefix PREFIX] [--duration DURATION] bucketName
```

### 1.15.1 Positional Arguments

**bucketName**

### 1.15.2 Named Arguments

**--prefix**            Default: “”

**--duration**          Default: 86400

## 1.16 Get-download-url-with-auth command

Prints a URL to download the given file. The URL includes an authorization token that allows downloads from the given bucket for files whose names start with the given file name.

The URL will work for the given file, but is not specific to that file. Files with longer names that start with the give file name can also be downloaded with the same auth token.

The token is valid for the duration specified, which defaults to 86400 seconds (one day).

Requires capability:

- **shareFiles**

```
b2 get-download-url-with-auth [-h] [--duration DURATION] bucketName fileName
```

### 1.16.1 Positional Arguments

**bucketName**

**fileName**

### 1.16.2 Named Arguments

**--duration**

Default: 86400

## 1.17 Get-file-info command

Prints all of the information about the file, but not its contents.

Requires capability:

- **readFiles**

```
b2 get-file-info [-h] fileId
```

### 1.17.1 Positional Arguments

**fileId**

## 1.18 Hide-file command

Uploads a new, hidden, version of the given file.

Requires capability:

- **writeFiles**

```
b2 hide-file [-h] bucketName fileName
```

### 1.18.1 Positional Arguments

**bucketName**

**fileName**

## 1.19 List-buckets command

Lists all of the buckets in the current account.

Output lines list the bucket ID, bucket type, and bucket name, and look like this:

```
98c960fd1cb4390c5e0f0519  allPublic  my-bucket
```

Alternatively, the `--json` option produces machine-readable output similar (but not identical) to the server api response format.

Requires capability:

- **listBuckets**

```
b2 list-buckets [-h] [--json]
```

### 1.19.1 Named Arguments

**--json**

Default: False

## 1.20 List-keys command

Lists the application keys for the current account.

The columns in the output are:

- ID of the application key
- Name of the application key
- Name of the bucket the key is restricted to, or – for no restriction



- Date of expiration, or –
- Time of expiration, or –
- File name prefix, in single quotes
- Command-separated list of capabilities

None of the values contain whitespace.

For keys restricted to buckets that do not exist any more, the bucket name is replaced with `id=<bucketId>`, because deleted buckets do not have names any more.

Requires capability:

- **listKeys**

```
b2 list-keys [-h] [--long]
```

### 1.20.1 Named Arguments

**--long**

Default: False

## 1.21 List-parts command

Lists all of the parts that have been uploaded for the given large file, which must be a file that was started but not finished or canceled.

Requires capability:

- **writeFiles**

```
b2 list-parts [-h] largeFileId
```

### 1.21.1 Positional Arguments

**largeFileId**

## 1.22 List-unfinished-large-files command

Lists all of the large files in the bucket that were started, but not finished or canceled.

Requires capability:

- **listFiles**

```
b2 list-unfinished-large-files [-h] bucketName
```

### 1.22.1 Positional Arguments

**bucketName**

## 1.23 Ls command

Using the file naming convention that / separates folder names from their contents, returns a list of the files and folders in a given folder. If no folder name is given, lists all files at the top level.

The `--long` option produces very wide multi-column output showing the upload date/time, file size, file id, whether it is an uploaded file or the hiding of a file, and the file name. Folders don't really exist in B2, so folders are shown with `-` in each of the fields other than the name.

The `--json` option produces machine-readable output similar to the server api response format.

The `--versions` option shows all versions of each file, not just the most recent.

The `--recursive` option will descend into folders, and will show only files, not folders.

Requires capability:

- **listFiles**

```
b2 ls [-h] [--long] [--json] [--versions] [--recursive]
      bucketName [folderName]
```

### 1.23.1 Positional Arguments

**bucketName**

**folderName**

### 1.23.2 Named Arguments

<b>--long</b>	Default: False
<b>--json</b>	Default: False
<b>--versions</b>	Default: False
<b>--recursive</b>	Default: False

## 1.24 Make-friendly-url command

Prints a short URL that can be used to download the given file, if it is public.

```
b2 make-friendly-url [-h] bucketName fileName
```

### 1.24.1 Positional Arguments

**bucketName**

**fileName**

## 1.25 Make-url command

Prints an URL that can be used to download the given file, if it is public.

```
b2 make-url [-h] fileId
```

### 1.25.1 Positional Arguments

**fileId**

## 1.26 Sync command

Copies multiple files from source to destination. Optionally deletes or hides destination files that the source does not have.

The synchronizer can copy files:

- From a B2 bucket to a local destination.
- From a local source to a B2 bucket.
- From one B2 bucket to another.
- Between different folders in the same B2 bucket.

Use `b2://<bucketName>/<prefix>` for B2 paths, e.g. `b2://my-bucket-name/a/path/prefix/`.

Progress is displayed on the console unless `--noProgress` is specified. A list of actions taken is always printed.

Specify `--dryRun` to simulate the actions that would be taken.

To allow sync to run when the source directory is empty, potentially deleting all files in a bucket, specify `--allowEmptySource`. The default is to fail when the specified source directory doesn't exist or is empty. (This check only applies to version 1.0 and later.)

Users with high-performance networks, or file sets with very small files, will benefit from multi-threaded uploads. The default number of threads is 10. Experiment with the `--threads` parameter if the default is not working well.

Users with low-performance networks may benefit from reducing the number of threads. Using just one thread will minimize the impact on other users of the network.

---

**Note:** Note that using multiple threads will usually be detrimental to the other users on your network.

---

You can specify `--excludeRegex` to selectively ignore files that match the given pattern. Ignored files will not copy during the sync operation. The pattern is a regular expression that is tested against the full path of each file.

You can specify `--includeRegex` to selectively override ignoring files that match the given `--excludeRegex` pattern by an `--includeRegex` pattern. Similarly to `--excludeRegex`, the pattern is a regular expression that is tested against the full path of each file.

---

**Note:** Note that `--includeRegex` cannot be used without `--excludeRegex`.

---

You can specify `--excludeAllSymlinks` to skip symlinks when syncing from a local source.

When a directory is excluded by using `--excludeDirRegex`, all of the files within it are excluded, even if they match an `--includeRegex` pattern. This means that there is no need to look inside excluded directories, and you can exclude directories containing files for which you don't have read permission and avoid getting errors.

The `--excludeDirRegex` is a regular expression that is tested against the full path of each directory. The path being matched does not have a trailing `/`, so don't include on in your regular expression.

Multiple regex rules can be applied by supplying them as pipe delimited instructions. Note that the regex for this command is Python regex. Reference: <https://docs.python.org/2/library/re.html>

Regular expressions are considered a match if they match a substring starting at the first character. `.*e` will match `hello`. This is not ideal, but we will maintain this behavior for compatibility. If you want to match the entire path, put a `$` at the end of the regex, such as `.*llo$`.

You can specify `--excludeIfModifiedAfter` to selectively ignore file versions (including hide markers) which were synced after given time (for local source) or ignore only specific file versions (for b2 source). Ignored files or file versions will not be taken for consideration during sync. The time should be given as a seconds timestamp (e.g. "1367900664") If you need milliseconds precision, put it after the comma (e.g. "1367900664.152")

Files are considered to be the same if they have the same name and modification time. This behaviour can be changed using the `--compareVersions` option. Possible values are:

- `none`: Comparison using the file name only
- `modTime`: Comparison using the modification time (default)
- `size`: Comparison using the file size

A future enhancement may add the ability to compare the SHA1 checksum of the files.

Fuzzy comparison of files based on `modTime` or `size` can be enabled by specifying the `--compareThreshold` option. This will treat `modTimes` (in milliseconds) or `sizes` (in bytes) as the same if they are within the comparison threshold. Files that match, within the threshold, will not be synced. Specifying `--verbose` and `--dryRun` can be useful to determine comparison value differences.

When a destination file is present that is not in the source, the default is to leave it there. Specifying `--delete` means to delete destination files that are not in the source.

When the destination is B2, you have the option of leaving older versions in place. Specifying `--keepDays` will delete any older versions more than the given number of days old, based on the modification time of the file. This option is not available when the destination is a local folder.

Files at the source that have a newer modification time are always copied to the destination. If the destination file is newer, the default is to report an error and stop. But with `--skipNewer` set, those files will just be skipped. With `--replaceNewer` set, the old file from the source will replace the newer one in the destination.

To make the destination exactly match the source, use:

```
b2 sync --delete --replaceNewer ... ..
```

**Warning:** Using `--delete` deletes files! We recommend not using it. If you use `--keepDays` instead, you will have some time to recover your files if you discover they are missing on the source end.

To make the destination match the source, but retain previous versions for 30 days:

```
b2 sync --keepDays 30 --replaceNewer ... b2://...
```

Example of sync being used with `--excludeRegex`. This will ignore `.DS_Store` files and `.Spotlight-V100` folders:

```
b2 sync --excludeRegex '(*\.DS_Store)|(*\.Spotlight-V100)' ... b2://...
```

To request SSE-B2 encryption for destination files, please set `--destinationServerSideEncryption=SSE-B2`. The default algorithm is set to AES256 which can be changed with `--destinationServerSideEncryptionAlgorithm` parameter.

Requires capabilities:

- **listFiles**
- **readFiles** (for downloading)
- **writeFiles** (for uploading)

```
b2 sync [-h] [--noProgress] [--dryRun] [--allowEmptySource]
      [--excludeAllSymlinks] [--threads THREADS]
      [--compareVersions {none,modTime,size}] [--compareThreshold MILLIS]
      [--excludeRegex REGEX] [--includeRegex REGEX]
      [--excludeDirRegex REGEX] [--excludeIfModifiedAfter TIMESTAMP]
      [--destinationServerSideEncryption {SSE-B2}]
      [--destinationServerSideEncryptionAlgorithm {AES256}]
      [--skipNewer | --replaceNewer] [--delete | --keepDays DAYS]
      source destination
```

### 1.26.1 Positional Arguments

**source**

**destination**

### 1.26.2 Named Arguments

- noProgress**      Default: False
- dryRun**          Default: False
- allowEmptySource** Default: False
- excludeAllSymlinks** Default: False
- threads**          Default: 10
- compareVersions**   Possible choices: none, modTime, size  
Default: "modTime"
- compareThreshold**

**--excludeRegex**      Default: []  
**--includeRegex**      Default: []  
**--excludeDirRegex**   Default: []  
**--excludeIfModifiedAfter**  
**--destinationServerSideEncryption**   Possible choices: SSE-B2  
**--destinationServerSideEncryptionAlgorithm**   Possible choices: AES256  
   Default: "AES256"  
**--skipNewer**            Default: False  
**--replaceNewer**        Default: False  
**--delete**              Default: False  
**--keepDays**

## 1.27 Update-bucket command

Updates the `bucketType` of an existing bucket. Prints the ID of the bucket updated.

Optionally stores bucket info, CORS rules and lifecycle rules with the bucket. These can be given as JSON on the command line.

If you want server-side encryption for all of the files that are uploaded to a bucket, you can enable SSE-B2 encryption as a default setting for the bucket. In order to do that pass `--defaultServerSideEncryption=SSE-B2`. The default algorithm is set to AES256 which can be changed with `--defaultServerSideEncryptionAlgorithm` parameter. All uploads to that bucket, from the time default encryption is enabled onward, will then be encrypted with SSE-B2 by default.

To disable default bucket encryption, use `--defaultServerSideEncryption=none`.

If `--defaultServerSideEncryption` is not provided, default server side encryption is determined by the server.

---

**Note:** Note that existing files in the bucket are not affected by default bucket encryption settings.

---

Requires capability:

- **writeBuckets**
- **readBucketEncryption**
- **writeBucketEncryption**

```
b2 update-bucket [-h] [--bucketInfo BUCKETINFO] [--corsRules CORSRULES]
                  [--lifecycleRules LIFECYCLERULES]
                  [--defaultServerSideEncryption {SSE-B2,none}]
                  [--defaultServerSideEncryptionAlgorithm {AES256}]
                  bucketName bucketType
```

### 1.27.1 Positional Arguments

**bucketName**

**bucketType**

### 1.27.2 Named Arguments

**--bucketInfo**

**--corsRules**

**--lifecycleRules**

**--defaultServerSideEncryption** Possible choices: SSE-B2, none

**--defaultServerSideEncryptionAlgorithm** Possible choices: AES256

Default: "AES256"

## 1.28 Upload-file command

Uploads one file to the given bucket. Uploads the contents of the local file, and assigns the given name to the B2 file.

By default, `upload_file` will compute the sha1 checksum of the file to be uploaded. But, if you already have it, you can provide it on the command line to save a little time.

Content type is optional. If not set, it will be set based on the file extension.

By default, the file is broken into as many parts as possible to maximize upload parallelism and increase speed. The minimum that B2 allows is 100MB. Setting `--minPartSize` to a larger value will reduce the number of parts uploaded when uploading a large file.

The maximum number of upload threads to use to upload parts of a large file is specified by `--threads`. It has no effect on small files (under 200MB). Default is 10.

If the `tqdm` library is installed, progress bar is displayed on stderr. Without it, simple text progress is printed. Use `--noProgress` to disable progress reporting.

Each `fileInfo` is of the form `a=b`.

To request SSE-B2 encryption for destination files, please set `--destinationServerSideEncryption=SSE-B2`. The default algorithm is set to AES256 which can be changed with `--destinationServerSideEncryptionAlgorithm` parameter.

Requires capability:

- **writeFiles**

```
b2 upload-file [-h] [--noProgress] [--quiet] [--contentType CONTENTTYPE]
               [--minPartSize MINPARTSIZE] [--sha1 SHA1] [--threads THREADS]
               [--info INFO] [--destinationServerSideEncryption {SSE-B2}]
               [--destinationServerSideEncryptionAlgorithm {AES256}]
               bucketName localFilePath b2FileName
```

### 1.28.1 Positional Arguments

**bucketName**

**localFilePath**

**b2FileName**

### 1.28.2 Named Arguments

**--noProgress**           Default: False

**--quiet**                Default: False

**--contentType**

**--minPartSize**

**--sha1**

**--threads**             Default: 10

**--info**                Default: []

**--destinationServerSideEncryption**   Possible choices: SSE-B2

**--destinationServerSideEncryptionAlgorithm**   Possible choices: AES256

Default: "AES256"

## 1.29 Version command

Prints the version number of this tool.

```
b2 version [-h]
```



## INDICES AND TABLES

- `genindex`
- `modindex`
- `search`